


METHYS

FEATURES

- Fast Curing
- Flexible Roll to Roll ink designed for flexible medias
- Designed for LED and Mercury UV lamps
- Good gloss levels
- Suitable for high speed printing
- Designed to be NVC Free



A56 F&F



OVERVIEW

Amethyst A56-MP-F&F is a flexible, fast curing UV ink suitable for LED as well as Mercury Vapour UV lamps and designed for self-adhesive as well as flexible medias.

The A56-MP-F&F performs well in a demanding, high speed printing environment. The ink is NVC free ensuring the product is compliant with future regulation requirements.

This formula is designed for compatibility across a broad range of print head models and features a superior colour gamut for bright, vivid images.

Provided the inks are used in regular applications, using suitable substrates, the printed images will not fade unduly for up to two years.


SPECIFICATIONS

Media range	9.5	Flexibility 8	3.5
Permanence	9.5	Colour gamut	10
Odour	9*	Adhesion	8
Stretchability	6	CNC cutting ability	9
Curing rate	9.5	Chemical resistance	8
Surface hardness 8.5			



A56-MP-F&F

*10= Low Odour



**KM512 14pl, KM1024 14pl, Spectra Galaxy JA 256/30, Spectra Galaxy JA 256/50, Spectra Nova JA 256/80, Spectra SE 128 (30pl), Spectra SL 128 (80pl), Spectra SM 128 (50pl), Spectra Polaris PQ-512/15, Spectra Polaris PQ-512/35, Ricoh Gen3-E3, Ricoh Gen4-E1, Ricoh Gen5-E1, Xaar 500/40 (40pl) UV, CA4 (UV) 6pl-42pl

PACKAGING CONFIGURATIONS 1L, 3L, 5L

SHELF LIFE 12 months (CMYKLcLm)

SHIPPING AND STORAGE Storage & transit temperatures: +5°C to +35°C **INFORMATION**

Store in a cool, dry area, not directly on the floor and away from direct sunlight

OPERATING SPECIFICATIONS Temperature: +19°C to +28°C

Relative Humidity: 30% to 80% Non-condensing

Ref.no. NU A56-MP-F&F 2015.04. All trademarks recognised. E&OE.

**Colour Profiling and possible machine setting adjustment required

