

Theatre FR

190gsm

Material Description High quality polyester woven textile. This textile is Fire retardent, and fray free when cutting it. It gives vibrant colours and instant drying due to it's inkjet coating. No edge curling & no cracking with framing. Cross compatible with all inks, but gives best results with water-based in latex inks.

- Qualifications**
- A fine Matt coated finish
 - Available in 103cm - 505cm.
 - Vibrant colours & Instant drying
 - Fire retardant, Anti fraying & clean cut
 - No edge curling & no cracking
 - Weight 190gsm
 - Tear resistant

- Details**
- Suitable printing condition: temperature 15-30°C / humidity 30-60%
 - Dye based inks and pigmented inks are compatible
 - Over (liquid) laminating prolongs the lifetime of the print
 - Ambient temperature and weather can affect the condition of the product





- Applications**
- Frame systems
 - Banners
 - Scenography

Physical Properties

| | | |
|----------------|--|--|
| Quality | | High quality 100% PES |
| Weight | | 190g/m ² ± 5 g/m ² |
| Print side | | Matt Instant dry coating for Solvent and UV ink |
| Reverse side | | White matt for Dye sublimation and direct printing |
| Fire retardent | | Yes , B1 |
| Anti curl | | Yes |
| Fray free | | Yes |
| | | |
| | | |
| | | |

Compatibility

Hewlett packard
Epson
Canon/ Oce
And more...

-  Solvent
-  WB dye sub & direct
-  LATEX
-  UV Curable

Make your own practical test to be sure it reaches your quality standard.
For all- and latest information see our Compatibility List.

Printing guidelines

Ink restrictions and heater settings have to be set for specific printer ink combinations to obtain the best results. Front side is coated for Solvent and UV inks, and at back is open fabric for dye direct and sublimation printing.

Colour profiles

TEPEDE develops high quality ICC colour profiles for the divers printing media's. We work with specialists who can produce your profile if it's not direct available from our library. Please contact us for the possibilities.

Storage conditions

1 year under normal conditions (10–25°C at a relative humidity of 50 %). Higher humidity and/or temperature can affect the product performance. Always store the media in a dark place.

Environment

The media and final prints can be disposed of as polyester. Material is suitable for recycling. Please consult local recycle resources.