

PRODUCT DATA SHEET

PRODUCT DESCRIPTION:	Flexible Magnetic Sheeting with Matt White PET Film
STANDARD THICKNESS¹:	0.2mm, 0.3mm (+/-0.03mm)
STANDARD WIDTH:	1270mm, 1370mm, 1520mm (+4mm/-0)
STANDARD LENGTH:	30M (+0.2M/-0)

MAGNETIC POLE WIDTH AND MAGNETIC PULL

<u>Magnetic Thickness</u>	<u>Magnetic Pole Width</u>	<u>Magnetic Pull</u>
0.2mm	1.5mm	≥ 10 g/cm ²
0.3mm	1.5mm	≥ 13 g/cm ²

PHYSICAL PROPERTIES

Flexibility: can be wrapped around a rod with a 12mm radius at 20°C without cracking.
Cutting: Scissor cutting, knife-cutting, die-cutting, and slitting can be done with ease.

TEMPERATURE RESISTANCE

End-use temperature range: - 20°C / + 50°C
Short term resistance: 65°C

BACKCOATING: The magnetic sheeting has no UV hardened coating on the magnetic side.

PET FILM

Printability:

Large Format Digital Printer: Solvent-based inks	Yes
Large Format Digital Printer: UV inks	Yes

Notes:

1. Thickness refers to magnetic thickness, PVC thickness is 0.1mm
2. Users should do preliminary tests to confirm printability before production. Printing problems may occur on certain machines due to ink problems or other technical problems not to our knowledge.

IMPORTANT NOTICE

Published information concerning TEPEDE products is based upon research and information which the Company believes to be reliable although such information does not constitute a warranty. Because of the variety of uses of TEPEDE products and the continuing development of new applications, the purchaser should carefully consider the suitability and performance of the product for each intended use, and the purchaser shall assume all risks regarding such use. The seller shall not be liable for damages in excess of the purchase price of the product nor for incidental or consequential damages. All specifications are subject to change without prior notice. TEPEDE October 2015.



Vodovodna 20a
10000 Zagreb, Hrvatska
+385/0/ 1 364 36 41
www.tepede.hr
prodaja@tepede.hr